KUBOTA M1085

DIESEL TRACTOR



Turbocharged with Intercooler for Optimum Power in a Sleek, New, Stylish Design!

SPECIFICATIONS

ENGINE

Model	V3800-DI-TI
Туре	Vertical, water-cooled, 4-cycle diesel engine
No. of cylincder	4
Net power	79.4 Kw (106 Hp)
Battery	12 V
Fuel tank	175 L

DIMENSIONS

Overall length		4065 mm
Overall width (minimum tread)		2220 mm
Overall height		2675 mm
Wheel base		2435 mm
Tread	Front	1550 mm, 1650 mm
	Rear	1760 to 2090 mm
Minimum ground clearance		435 mm (drawbar bracket)
Weight		3650 kg

NOTE: All M-series tractors are equipped with vertical muffler and safety emblem

TRAVELING SYSTEM

Standard tire size	Front	13.6-24	
	Rear	18.4-34	
Clutch		Hydraulic wet discs	
Steering		Hydraulic shuttle shift, fully synchronized main shift, 16F/16R	
Brake	Travelling	Wet type multiple discs (hydraulic)	
	Parking	Wet type multiple discs (mechanical)	
Differential		Bevel gears with differential lock (front and rear)	

HYDRAULIC UNIT

Hydraulic control system	Position, draft and mix control
Pump capacity	65.0L/ min.
Three point hitch	Category 2

PTO SYSTEM

Independent of	clutch system	Wet type, multiple discs
Indepent PTO	Direction of turning	Clockwise, viewed from tractor rear
	PTO speed	6 spline : 540 (rpm)
Traction syste	m	Swing drawbar, adjustable in direction

WORKS PERFECTLY WITH THE FOLLOWING IMPLEMENT

OPERATIONAL CONTROLS

TRANSMISSION CONTROLS



Sugarcane Planter

Model	SP920
Implement Work	Planting Sugarcane Stem
Implement work	with Double Row
Stem Length	350 to 400 (mm)
Sugarcane Capacity	850 kg
Fertilizer Tank Capacity	50 kg
Dimension (WxLxH)	1874 x 2095 x 2245 (mm)
Body Weight	933 kg



ADJUSTABLE STEERING WHEEL















f ◎ **D J** Kubota Philippines



For details and inquiries:

Main Office:

Kubota Philippines, Inc. 232 Quirino Highway, Baesa, Quezon City, Metro Manila (632) 8422-3500 to 03 (632) 8422-3504 to 05

Tel. Nos.: Fax Nos.: Website: https://kubota.com.ph **Authorized Dealer:**