# KUBOTA SPV-6CMD

**Rice Transplanter** 



For fast, high-precision transplanting to fully increase productivity and ensure tip-top quality harvest!

# **SPECIFICATIONS**

# **DIMENSIONS**

Туре		Automatic leveling control
Drive System		4 - wheel drive
Dimension	Overall length	3050 mm
	Overall width	2220 mm
	Overall height	1805 mm
	Minimum ground clearance	500 mm
Weight		805 kg

# **ENGINE**

Model	D782-E3-P-4
Туре	Water-Cooled, 4-Cycle, 3-Cylinder
Туре	Vertical Type Diesel Engine
Output	14.41 kW (19.33 Hp)
Fuel	Diesel Fuel
Fuel tank capacity	34 L
Battery	12 V

# **SEEDLING CONDITIONS**

Seedling type	Seedling mat
Seedling height	8 - 25 cm
Number of leaves	2.0 to 4.5 leaves

#### TRAVELING PORTION

Tires	Туре	Front	No-puncture tire
		Rear	Rubber lug wheel with thick rim
	Outer Diameter	Front	650 x 95 mm
		Rear	950 x 50 mm
	Tread	Front	1200 mm
		Rear	1200 mm
Steering system			Integral power steering
Shifting system			Hydrostatic transmission (HST)
Number of shifting positions			HST main shift: variable speeds for
			forward and reverse


# **PLANTING PORTION**

Planting system		Rotary, forced planting
Number of planting rov	/S	6
Hill space		30 cm
Row distance		*10, 12, 14, 16, 21, 24 cm
Planting depth		1 to 5.5 cm (7 position)
Number of	Crossfeed distance/	11 mm / 26 times, 14 mm / 20 times,
Seedling per hill	crossfeed times	16 mm / 18 times, 18 mm / 16 times
Seeding per niii	Taking Quantity	8 to 18 mm


# **High Ground Clearance**



# **MUD Cover**



# **Additional Tray Platform**




Planting depth adjustment lever

Easy Stop Lever



# Hills space adjusting lever











f 💿 🗗 J Kubota Philippines



# For details and inquiries:

Main Office:

Kubota Philippines, Inc. 232 Quirino Highway, Baesa, Quezon City, Metro Manila

(632) 8422-3500 to 03 (632) 8422-3504 to 05 Tel. Nos.: Fax Nos.: Website: https://kubota.com.ph

#### **Authorized Dealer:**